



Form A - EN 175301-803 (DIN43650) / ISO 4400

Product description			
Standard	EN175301-803	EN175301-803	
Construction type	A	A	
Description	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and protective circuit (diode)	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and protective circuit (diode)	
Housing colour	transparent	transparent	
Number of contacts	2+PE	2+PE	
Order no.	KA132D54T9	KA132D54T1	
Other options on request	led colour red led colour green	order no. KA132D57T9 order no. KA132D5AT9	order no. KA132D57T1 order no. KA132D5AT1
Cable gland	PG9 (M16x1,5 on request)	PG11	
Max. conductor size	1,5mm ² without splice/terminal	1,5mm ² without splice/terminal	
Drawing			
Technical data			
Pin dimension	6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm	
Voltage	24 V DC	24 V DC	
Rated current max.	4 A	4 A	
Suppressor	Diode 1A 1000V	Diode 1A 1000V	
LED colour	yellow	yellow	
Contact resistance	15mΩ max.	15mΩ max.	
Overvoltage category	III	III	
Type of termination	screw M3	screw M3	
Contact screw torque	max. 0,5 N/m	max. 0,5 N/m	
Suitable cables	5 mm to 7 mm diameter	6 mm to 9 mm diameter	
Mounting	central screw M3x32,5	central screw M3x32,5	
Material			
Contact holder material	PA6 GF	PA6 GF	
Housing material	PA12	PA12	
Environmental conditions			
Protection class (EN 60529)	IP 65 when correctly assembled	IP 65 when correctly assembled	
Pollution severity (EN 60664-1)	3	3	
Temperature range	-20°C to + 80°C	-20°C to + 80°C	
Inflammability class			
Contact holder	HB - UL 94	HB - UL 94	
Housing	HB - UL 94	HB - UL 94	
Packaging			
Packaging unit / Weight approx.	100 pieces / 2,5Kg	100 pieces / 2,5Kg	
Box dimensions	29 x 15 x 18 cm	29 x 15 x 18 cm	
Other accessories options			
to be ordered separately see pages 171-175	NBR flat gasket 100 pcs in bag Silicon profile gasket 100 pcs in bag Stainless steel screw 100 pcs in bag	NBR flat gasket 100 pcs in bag Silicon profile gasket 100 pcs in bag Stainless steel screw 100 pcs in bag	

Valve Connectors KA1 series

SELF - ASSEMBLY CABLE



EN175301-803	EN175301-803	EN175301-803	EN175301-803
A	A	A	A
P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and TVS protective circuit (transil)	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and TVS protective circuit (transil)	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and RC protective circuit	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and RC protective circuit
transparent	transparent	transparent	transparent
2+PE	2+PE	2+PE	2+PE
KA132T54T9	KA132T54T1	KA132C54T9	KA132C54T1
order no. KA132T57T9	order no. KA132T57T1		
order no. KA132T5AT9	order no. KA132T5AT1		
PG9 (M16x1,5 on request)	PG11	PG9 (M16x1,5 on request)	PG11
1,5mm ² without splice/terminal	1,5mm ² without splice/terminal	1,5mm ² without splice/terminal	1,5mm ² without splice/terminal
6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm
24 V AC/DC	24 V AC/DC	24 V AC/DC	24 V AC/DC
4 A	4 A	4 A	4 A
TVS Vbr max.=37,8V Peak=400W	TVS Vbr max.=37,8V Peak=400W	Filter RC C=0,1 µF R=100 Ω	Filter RC C=0,1 µF R=100 Ω
yellow	yellow	yellow	yellow
15mΩ max.	15mΩ max.	15mΩ max.	15mΩ max.
III	III	III	III
screw M3	screw M3	screw M3	screw M3
max. 0,5 N/m	max. 0,5 N/m	max. 0,5 N/m	max. 0,5 N/m
5 mm to 7 mm diameter	6 mm to 9 mm diameter	5 mm to 7 mm diameter	6 mm to 9 mm diameter
central screw M3x32,5	central screw M3x32,5	central screw M3x32,5	central screw M3x32,5
PA6 GF	PA6 GF	PA6 GF	PA6 GF
PA12	PA12	PA12	PA12
IP 65 when correctly assembled	IP 65 when correctly assembled	IP 65 when correctly assembled	IP 65 when correctly assembled
3	3	3	3
-20°C to + 80°C	-20°C to + 80°C	-20°C to + 80°C	-20°C to + 80°C
HB - UL 94	HB - UL 94	HB - UL 94	HB - UL 94
HB - UL 94	HB - UL 94	HB - UL 94	HB - UL 94
100 pieces / 2,5Kg	100 pieces / 2,5Kg	100 pieces / 2,5Kg	100 pieces / 2,5Kg
29 x 15 x 18 cm	29 x 15 x 18 cm	29 x 15 x 18 cm	29 x 15 x 18 cm
NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag
Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag
Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag

Form A - EN 175301-803 (DIN43650) / ISO 4400