21.8  $\infty$ 5 5.8 11.6 Ø.0.8 2 3 2 0 SECTION I-I

THIS SERIES FULLY CONFORMS TO THE

**EUROPEAN UNION DIRECTIVES** 

2011/65/EU FOR RoHS COMPLIANCY

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER ORIGINAL


1

MATERIALS:

HOUSING: PBT, UL94V-0, BLUE COLOR TERMINAL: BRASS, TIN PLATED

## **SPECIFICATIONS**

- PITCH: 5.8MM
- **RATED VOLTAGE: 300V**
- 2. 3. RATED CURRENT: 10A MAX
- WITHSTAND VOLTAGE: AC1700V R.M.S.
- CONTACT RESISTANCE: 10 mOHMS MAX INSULATION RESISTANCE: 1000 MOHMS
  - MIN/DC 500V
- TEMPERATURE RANGE: -40°C ~ +105°C
- WATERPROOF GRADE: TESTED AND **CERTIFIED TO IP67**



RECOMMENDED PCB HOLE

ITEM NO.	DESCRIPTION	QTY.
1	570-420 PCB-TERMINAL-1	3
2	572-003-420-PCB HOUSING	1

Waterproof Connector, PCB Mount, Male, Blue, 3Pin 572-003-420-301

**EDAC INC** TORONTO, ONTARIO

CANADA

YOUR CONNECTION TO QUALITY & SERVICE

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC., AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:R.STA.MONICA DATE: NOV.16/15 CHECKED: DATE: SCALE: NOT TO SCALE SHEET 1 OF 1 DRAWING NUMBER **ISSUE** 572-003-420-301

572-003-420-301

ACAD REFERENCE NO.